




PASSIVE FLOCCULANT DOSING SYSTEM FOR CONSTRUCTION SITE IMPLEMENTATION

**By Karl Garbrecht, Jason Vogel, Dan Storm,
and Bill Barfield**



AGENDA



1. Current Flocculation Methods
2. Project Objectives
3. Apparatus Description
4. Experimental Testing
5. Results and Conclusion

TRADITIONAL SEDIMENT CAPTURE STRATEGIES



Traditional Strategies

- Rely on gravity settling
- Require large volumes for sufficient retention time
- Can be ineffective

Improved Strategies

- Incorporate waste water treatment technologies to enhance sediment capture




ENHANCED SEDIMENT CAPTURE VIA FLOCCULATION



Flocculation

- Bridges multiple particles together to form flocs
- Polymers used as bridging agents
- Polymers sold as powders, solids, or liquid
- Flocculant concentration and mixing intensity essential for optimum flocculation



CURRENT PASSIVE FLOCCULATION TECHNIQUES



Pros

- Easy installation
- Low cost
- Proven effective

Challenges

- Limited data on dosing concentrations
- Potential to become sediment laden




PROJECT OBJECTIVES



Develop a flocculant injection system for construction site implementation which must be:


- 1) Automated
- 2) Standalone/passive
- 3) Capable of maintaining optimum dosing concentrations

ALTERNATIVE 1: NEW ZEALAND SYSTEM




Rain is collected and routed into a bucket which displaces liquid flocculant into runoff


ALTERNATIVE 1: NEW ZEALAND SYSTEM



ALTERNATIVE 2: OSU SYSTEM



Dosing Apparatus



As forebay stage increases additional floats are actuated which correspond to increasing flow through flow control structure

COMPARISON



Similarities

- Automated
- Standalone and passive
- Maintain dosing concentrations
- Portable

N.Z. System vs. OSU System


- Rainfall Controlled vs. Runoff Controlled
- Site specific design vs. General design
- No Moving Parts vs. Float Valves

MODELING COMPARISON




N.Z. System

Sensitive to
rainfall runoff
relationship



OSU System

Number of floats
determine
dosing range



MODELING CONCLUSION





The OSU Experimental System

- Maintains optimum dosing concentrations
- Does not rely on unique rainfall/runoff modeling for dosing
 - Dynamic site characteristic do not influence performance
 - Structure can be reused without alteration for sites with similar runoff rates
 - Rapid calibration


OSU SYSTEM





OSU SYSTEM



OSU SYSTEM



OSU SYSTEM




EXPERIMENTAL SET-UP



Sediment
Introduction

Initial
turbidity
samples



Forebay

Flocculant
Dosing and
Mixing

EXPERIMENTAL SET-UP




4 Turbidity measurements 25 ft. apart




RESULTS


Sample Locations



Control (1.5 cfs)




Floc Test (1.5 cfs)




RESULTS



Control



Floc Test



RESULTS



**Inflow
Turbidity**

**2
4
0
0**

**No
Flocculant**


**1
9
2
0**

Flocculant

**4
8
0**



RESULTS



SUMMARY



Conclusions

- Demonstrated successful operation
- Apparatus achieved 4 x turbidity reduction compared to control
- Majority of turbidity reduction took place within 1 minute of settling time for all experiments

Future Work

- Modularize components
- Refine system and implement on construction site for performance monitoring



Patent Pending

ACKNOWLEDGMENTS



Research Team

Aaron Mittelstet	Neha Bhadbhade
Grant Graves	Hayatt Azawi
Alex Tobergte	Erin Daly

ARS Hydraulics Lab

Tyler	Greg Hanson
Bob	Kem Kadavy

Project Sponsors

Woolpert, Inc.

Greenville Co., SC

